

# HR CoaXPress

hr65CCX



## General

Model:	hr65CCX
Product code(s):	F004149
Product series:	HR CoaXPress
Status:	Available

## Sensor

Sensor type:	Area scan
Chroma:	Color
Spectrum:	Visible
Spectral range:	400 nm to 1000 nm
Resolution:	9,344 × 7,000 (65.00 MP)
Sensor model:	Gpixel GMAX3265
Sensor architecture (material):	cmos
Shutter type(s):	global-shutter
Sensor size:	29.90 × 22.40 mm (37.36 mm, 37.4mm)
Pixel size:	3.20 μm × 3.20 μm

## Pixel formats

Sensor bit depth:	8-Bit,10-Bit
RGB pixel formats:	bayer8, bayer10

## Imaging performance

Dynamic range: 65.6 dB

SNR: 40 dB

## Timing and gain

Max. frame rate: 35.5 fps

Exposure time: 60  $\mu$ s (max)

Gain: 0.0 dB to 18.0 dB

## I/Os and power

Non-isolated lines: 0 x LVDS input, 0 x LVDS output, 0 x TTL input, 0 x TTL output, 2 x 24V input, 4 x Open drain output

Specific non-isolated lines: 1 x RS232 input, 1 x RS232 output, 0 x RS422 input, 0 x RS422 output

Opto-isolated lines: 1 x Optical isolated input, 0 x Optical isolated Input,

Power supply: 10 to 25VDC

Power consumption: External: 10.5 W (typical at 12 VDC)

## Operating conditions

Operating temperature (housing): -10 °C to 65 °C

## Mechanical properties

Body dimensions (L x W x H in mm): 76 x 70 x 70

Filter/protection glass: IR-Cut 680

IP class: IP30

Lens mount(s): M58x0.75

Weight: 420 g

## On-board memory and FPGA

Non-volatile memory (Flash): 160 KByte

## Interfaces

Digital interface: cxp-6 with 4 connections

Interface connector: (Din1.0/2.3)

## FW features - image control

Exposure modes: Manual, Auto, External

Gain modes: Auto, Manual

White balance modes: auto, manual

## FW features - image control

Image control features:

FW Features - Image Control

## FW features - camera control

Trigger modes/sync:


INTERNAL,SOFTWARE,EXTERNAL

Camera control features:


PoCxP, User Sets, PWM(4), Sequencer,

## Color


(not included: lens- and light source characteristics)




front




back




cross section




right side





top



bottom




3D



## I/O pin assignment

Hirose 12 Pin



1	VIN -	(GND)	7	OUT 1	(open drain)
2	VIN +	(10 V to 25 V DC)	8	OUT 2	(open drain)
3	IN 4	(RXD RS232)	9	IN 3 +	(opto In +)
4	OUT 4	(TXD RS232)	10	IN 3 -	(opto In -)
5	IN 1	(0-24V)	11	OUT 3	(open drain)
6	IN 2	(0-24V)	12	OUT 0	(open drain)